











3wire DC 4pin connector PNP inductive sensor

housing					
	M12X1Ni PLATED Brass	M12X1Ni PLATED Brass	M12X1Ni PLATED Brass	M12X1Ni PLATED Brass	M12X1Ni PLATED Brass
code	IPS-302-CP-12-S4	IPS-302-CP-12-V-S4	IPS-302-OP-12-S4	IPS-302-OP-12-V-S4	IPS-304-CP-12-S4
number of wires	3	3	3	3	3
switching distance	2 mm	2 mm	2 mm	2 mm	4 mm
temperature range	-20~+60 °C	-20~+60 °C	-20~+60 °C	-20~+60 °C	-20~+60 °C
influence protection	IP66	IP66	IP66	IP66	IP66
output	4Pin SOCKET	4Pin SOCKET	4Pin SOCKET	4Pin SOCKET	4Pin SOCKET
output stage	PNP TRANSISTOR	PNP TRANSISTOR	PNP TRANSISTOR	PNP TRANSISTOR	PNP TRANSISTOR
output function	NC	NC	NO	NO	NC
voltage range	10-30VDC	10-60VDC	10-30VDC	10-60VDC	10-30VDC
max output current	250 mA	250 mA	250 mA	250 mA	250 mA
max output frequency	1500 Hz	1500 Hz	1500 Hz	1500 Hz	1500 Hz
indicator led	yes	yes	yes	yes	yes
max drop voltage	2 V	2 V	2 V	2 V	2 V
max no-load or leakage current	15 mA	15 mA	15 mA	15 mA	15 mA
pressure rate	3 bar	3 bar	3 bar	3 bar	3 bar
mounting	flush(shielded)	flush(shielded)	flush(shielded)	flush(shielded)	non flush (unshielded)
revers voltage protection	yes	yes	yes	yes	yes
short circuit protection	yes	yes	yes	yes	yes
pick voltage protection	yes	yes	yes	yes	yes
circuit					

Central office : No 36 , karimkhan ave. , darvazeh tehran , tabriz , iran ; zip code : 5157913399 ; P.O. box : 51575-5140
 Email : info@tabrizpeguh.com ; Website : www.tabrizpeguh.com ; Tel : +984133330490 ; Fax : +984133318200

3wire DC 4pin connector PNP inductive sensor

housing					
	M12X1Ni PLATED Brass	M12X1Ni PLATED Brass	M12X1Ni PLATED Brass	M14X1Ni PLATED Brass	M14X1Ni PLATED Brass
code	IPS-304-CP-12-V-S4	IPS-304-OP-12-S4	IPS-304-OP-12-V-S4	IPS-303-CP-14-S4	IPS-303-CP-14-V-S4
number of wires	3	3	3	3	3
switching distance	4 mm	4 mm	4 mm	3 mm	3 mm
temperature range	-20~+60 °C	-20~+60 °C	-20~+60 °C	-20~+60 °C	-20~+60 °C
influence protection	IP66	IP66	IP66	IP66	IP66
output	4Pin SOCKET	4Pin SOCKET	4Pin SOCKET	4Pin SOCKET	4Pin SOCKET
output stage	PNP TRANSISTOR	PNP TRANSISTOR	PNP TRANSISTOR	PNP TRANSISTOR	PNP TRANSISTOR
output function	NC	NO	NO	NC	NC
voltage range	10-60VDC	10-30VDC	10-60VDC	10-30VDC	10-60VDC
max output current	250 mA	250 mA	250 mA	250 mA	250 mA
max output frequency	1500 Hz	1500 Hz	1500 Hz	1500 Hz	1500 Hz
indicator led	yes	yes	yes	yes	yes
max drop voltage	2 V	2 V	2 V	2 V	2 V
max no-load or leakage current	15 mA	15 mA	15 mA	15 mA	15 mA
pressure rate	3 bar	3 bar	3 bar	3 bar	3 bar
mounting	non flush (unshielded)	non flush (unshielded)	non flush (unshielded)	flush(shielded)	flush(shielded)
revers voltage protection	yes	yes	yes	yes	yes
short circuit protection	yes	yes	yes	yes	yes
pick voltage protection	yes	yes	yes	yes	yes
circuit					

Central office : No 36 , karimkhan ave. , darvazeh tehran , tabriz , iran ; zip code : 5157913399 ; P.O. box : 51575-5140
 Email : info@tabrizpeguh.com ; Website : www.tabrizpeguh.com ; Tel : +984133330490 ; Fax : +984133318200

3wire DC 4pin connector PNP inductive sensor

housing					
	M14X1Ni PLATED Brass	M14X1Ni PLATED Brass	M14X1Ni PLATED Brass	M14X1Ni PLATED Brass	M14X1Ni PLATED Brass
code	IPS-303-OP-14-S4	IPS-303-OP-14-V-S4	IPS-305-CP-14-S4	IPS-305-CP-14-V-S4	IPS-305-OP-14-S4
number of wires	3	3	3	3	3
switching distance	3 mm	3 mm	5 mm	5 mm	5 mm
temperature range	-20~+60 °C	-20~+60 °C	-20~+60 °C	-20~+60 °C	-20~+60 °C
influence protection	IP66	IP66	IP66	IP66	IP66
output	4Pin SOCKET	4Pin SOCKET	4Pin SOCKET	4Pin SOCKET	4Pin SOCKET
output stage	PNP TRANSISTOR	PNP TRANSISTOR	PNP TRANSISTOR	PNP TRANSISTOR	PNP TRANSISTOR
output function	NO	NO	NC	NC	NO
voltage range	10-30VDC	10-60VDC	10-30VDC	10-60VDC	10-30VDC
max output current	250 mA	250 mA	250 mA	250 mA	250 mA
max output frequency	1500 Hz	1500 Hz	1000 Hz	1000 Hz	1000 Hz
indicator led	yes	yes	yes	yes	yes
max drop voltage	2 V	2 V	2 V	2 V	2 V
max no-load or leakage current	15 mA	15 mA	15 mA	15 mA	15 mA
pressure rate	3 bar	3 bar	3 bar	3 bar	3 bar
mounting	flush(shielded)	flush(shielded)	non flush (unshielded)	non flush (unshielded)	non flush (unshielded)
revers voltage protection	yes	yes	yes	yes	yes
short circuit protection	yes	yes	yes	yes	yes
pick voltage protection	yes	yes	yes	yes	yes
circuit					

Central office : No 36 , karimkhan ave. , darvazeh tehran , tabriz , iran ; zip code : 5157913399 ; P.O. box : 51575-5140
 Email : info@tabrizpeguh.com ; Website : www.tabrizpeguh.com ; Tel : +984133330490 ; Fax : +984133318200

3wire DC 4pin connector PNP inductive sensor

housing					
	M14X1Ni PLATED Brass	M18X1Ni PLATED Brass	M18X1Ni PLATED Brass	M18X1Ni PLATED Brass	M18X1Ni PLATED Brass
code	IPS-305-OP-14-V-S4	IPS-305-CP-18-S4	IPS-305-CP-18-VI-S4	IPS-305-CP-18-V-S4	IPS-305-OP-18-S4
number of wires	3	3	3	3	3
switching distance	5 mm	5 mm	5 mm	5 mm	5 mm
temperature range	-20~+60 °C	-20~+60 °C	-20~+60 °C	-20~+60 °C	-20~+60 °C
influence protection	IP66	IP66	IP66	IP66	IP66
output	4Pin SOCKET	4Pin SOCKET	4Pin SOCKET	4Pin SOCKET	4Pin SOCKET
output stage	PNP TRANSISTOR	PNP TRANSISTOR	PNP TRANSISTOR	PNP TRANSISTOR	PNP TRANSISTOR
output function	NO	NC	NC	NC	NO
voltage range	10-60VDC	10-30VDC	10-60VDC	10-60VDC	10-30VDC
max output current	250 mA	250 mA	450 mA	250 mA	250 mA
max output frequency	1000 Hz	700 Hz	700 Hz	700 Hz	700 Hz
indicator led	yes	yes	yes	yes	yes
max drop voltage	2 V	2 V	2 V	2 V	2 V
max no-load or leakage current	15 mA	15 mA	15 mA	15 mA	15 mA
pressure rate	3 bar	3 bar	3 bar	3 bar	3 bar
mounting	non flush (unshielded)	flush(shielded)	flush(shielded)	flush(shielded)	flush(shielded)
revers voltage protection	yes	yes	yes	yes	yes
short circuit protection	yes	yes	yes	yes	yes
pick voltage protection	yes	yes	yes	yes	yes
circuit					

Central office : No 36 , karimkhan ave. , darvazeh tehran , tabriz , iran ; zip code : 5157913399 ; P.O. box : 51575-5140
 Email : info@tabrizpeguh.com ; Website : www.tabrizpeguh.com ; Tel : +984133330490 ; Fax : +984133318200











3wire DC 4pin connector PNP inductive sensor

housing					
	M18X1Ni PLATED Brass	M18X1Ni PLATED Brass	M18X1Ni PLATED Brass	M18X1Ni PLATED Brass	M18X1Ni PLATED Brass
code	IPS-305-OP-18-VI-S4	IPS-305-OP-18-V-S4	IPS-308-OP-18-VI-S4	IPS-308-CP-18-S4	IPS-308-CP-18-VI-S4
number of wires	3	3	3	3	3
switching distance	5 mm	5 mm	8 mm	8 mm	8 mm
temperature range	-20~+60 °C	-20~+60 °C	-20~+60 °C	-20~+60 °C	-20~+60 °C
influence protection	IP66	IP66	IP66	IP66	IP66
output	4Pin SOCKET	4Pin SOCKET	4Pin SOCKET	4Pin SOCKET	4Pin SOCKET
output stage	PNP TRANSISTOR	PNP TRANSISTOR	PNP TRANSISTOR	PNP TRANSISTOR	PNP TRANSISTOR
output function	NO	NO	NO	NC	NC
voltage range	10-60VDC	10-60VDC	10-60VDC	10-30VDC	10-60VDC
max output current	450 mA	250 mA	450 mA	250 mA	450 mA
max output frequency	700 Hz	700 Hz	700 Hz	700 Hz	700 Hz
indicator led	yes	yes	yes	yes	yes
max drop voltage	2 V	2 V	2 V	2 V	2 V
max no-load or leakage current	15 mA	15 mA	15 mA	15 mA	15 mA
pressure rate	3 bar	3 bar	3 bar	3 bar	3 bar
mounting	flush(shielded)	flush(shielded)	non flush (unshielded)	non flush (unshielded)	non flush (unshielded)
revers voltage protection	yes	yes	yes	yes	yes
short circuit protection	yes	yes	yes	yes	yes
pick voltage protection	yes	yes	yes	yes	yes
circuit					

3wire DC 4pin connector PNP inductive sensor











housing					
	M18X1Ni PLATED Brass	M18X1Ni PLATED Brass	M18X1Ni PLATED Brass	M22X1.5Ni PLATED Brass	M22X1.5Ni PLATED Brass
code	IPS-308-CP-18-V-S4	IPS-308-OP-18-S4	IPS-308-OP-18-V-S4	IPS-308-CP-22-S4	IPS-308-CP-22-VI-S4
number of wires	3	3	3	3	3
switching distance	8 mm	8 mm	8 mm	8 mm	8 mm
temperature range	-20~+60 °C	-20~+60 °C	-20~+60 °C	-20~+60 °C	-20~+60 °C
influence protection	IP66	IP66	IP66	IP66	IP66
output	4Pin SOCKET	4Pin SOCKET	4Pin SOCKET	4Pin SOCKET	4Pin SOCKET
output stage	PNP TRANSISTOR	PNP TRANSISTOR	PNP TRANSISTOR	PNP TRANSISTOR	PNP TRANSISTOR
output function	NC	NO	NO	NC	NC
voltage range	10-60VDC	10-30VDC	10-60VDC	10-30VDC	10-60VDC
max output current	250 mA	250 mA	250 mA	250 mA	450 mA
max output frequency	700 Hz	700 Hz	700 Hz	500 Hz	500 Hz
indicator led	yes	yes	yes	yes	yes
max drop voltage	2 V	2 V	2 V	2 V	2 V
max no-load or leakage current	15 mA	15 mA	15 mA	15 mA	15 mA
pressure rate	3 bar	3 bar	3 bar	3 bar	3 bar
mounting	non flush (unshielded)	non flush (unshielded)	non flush (unshielded)	flush(shielded)	flush(shielded)
revers voltage protection	yes	yes	yes	yes	yes
short circuit protection	yes	yes	yes	yes	yes
pick voltage protection	yes	yes	yes	yes	yes
circuit					

3wire DC 4pin connector PNP inductive sensor

housing					
	M22X1.5Ni PLATED Brass	M22X1.5Ni PLATED Brass	M22X1.5Ni PLATED Brass	M22X1.5Ni PLATED Brass	M22X1.5Ni PLATED Brass
code	IPS-308-CP-22-V-S4	IPS-308-OP-22-S4	IPS-308-OP-22-VI-S4	IPS-308-OP-22-V-S4	IPS-310-CP-22-S4
number of wires	3	3	3	3	3
switching distance	8 mm	8 mm	8 mm	8 mm	10 mm
temperature range	-20~+60 °C	-20~+60 °C	-20~+60 °C	-20~+60 °C	-20~+60 °C
influence protection	IP66	IP66	IP66	IP66	IP66
output	4Pin SOCKET	4Pin SOCKET	4Pin SOCKET	4Pin SOCKET	4Pin SOCKET
output stage	PNP TRANSISTOR	PNP TRANSISTOR	PNP TRANSISTOR	PNP TRANSISTOR	PNP TRANSISTOR
output function	NC	NO	NO	NO	NC
voltage range	10-60VDC	10-30VDC	10-60VDC	10-60VDC	10-30VDC
max output current	250 mA	250 mA	450 mA	250 mA	250 mA
max output frequency	500 Hz	500 Hz	500 Hz	500 Hz	500 Hz
indicator led	yes	yes	yes	yes	yes
max drop voltage	2 V	2 V	2 V	2 V	2 V
max no-load or leakage current	15 mA	15 mA	15 mA	15 mA	15 mA
pressure rate	3 bar	3 bar	3 bar	3 bar	3 bar
mounting	flush(shielded)	flush(shielded)	flush(shielded)	flush(shielded)	non flush (unshielded)
revers voltage protection	yes	yes	yes	yes	yes
short circuit protection	yes	yes	yes	yes	yes
pick voltage protection	yes	yes	yes	yes	yes
circuit					











Central office : No 36 , karimkhan ave. , darvazeh tehran , tabriz , iran ; zip code : 5157913399 ; P.O. box : 51575-5140
 Email : info@tabrizpeguh.com ; Website : www.tabrizpeguh.com ; Tel : +984133330490 ; Fax : +984133318200

3wire DC 4pin connector PNP inductive sensor

housing					
	M22X1.5Ni PLATED Brass	M22X1.5Ni PLATED Brass	M22X1.5Ni PLATED Brass	M22X1.5Ni PLATED Brass	M22X1.5Ni PLATED Brass
code	IPS-310-CP-22-VI-S4	IPS-310-CP-22-V-S4	IPS-310-OP-22-S4	IPS-310-OP-22-VI-S4	IPS-310-OP-22-V-S4
number of wires	3	3	3	3	3
switching distance	10 mm	10 mm	10 mm	10 mm	10 mm
temperature range	-20~+60 °C	-20~+60 °C	-20~+60 °C	-20~+60 °C	-20~+60 °C
influence protection	IP66	IP66	IP66	IP66	IP66
output	4Pin SOCKET	4Pin SOCKET	4Pin SOCKET	4Pin SOCKET	4Pin SOCKET
output stage	PNP TRANSISTOR	PNP TRANSISTOR	PNP TRANSISTOR	PNP TRANSISTOR	PNP TRANSISTOR
output function	NC	NC	NO	NO	NO
voltage range	10-60VDC	10-60VDC	10-30VDC	10-60VDC	10-60VDC
max output current	450 mA	250 mA	250 mA	450 mA	250 mA
max output frequency	500 Hz	500 Hz	500 Hz	500 Hz	500 Hz
indicator led	yes	yes	yes	yes	yes
max drop voltage	2 V	2 V	2 V	2 V	2 V
max no-load or leakage current	15 mA	15 mA	15 mA	15 mA	15 mA
pressure rate	3 bar	3 bar	3 bar	3 bar	3 bar
mounting	non flush (unshielded)	non flush (unshielded)	non flush (unshielded)	non flush (unshielded)	non flush (unshielded)
revers voltage protection	yes	yes	yes	yes	yes
short circuit protection	yes	yes	yes	yes	yes
pick voltage protection	yes	yes	yes	yes	yes
circuit					











Central office : No 36 , karimkhan ave. , darvazeh tehran , tabriz , iran ; zip code : 5157913399 ; P.O. box : 51575-5140
 Email : info@tabrizpeguh.com ; Website : www.tabrizpeguh.com ; Tel : +984133330490 ; Fax : +984133318200

3wire DC 4pin connector PNP inductive sensor











housing					
	M30X1.5Ni PLATED Brass	M30X1.5Ni PLATED Brass	M30X1.5Ni PLATED Brass	M30X1.5Ni PLATED Brass	M30X1.5Ni PLATED Brass
code	IPS-310-CP-30-S4	IPS-310-CP-30-VI-S4	IPS-310-CP-30-V-S4	IPS-310-OP-30-S4	IPS-310-OP-30-VI-S4
number of wires	3	3	3	3	3
switching distance	10 mm	10 mm	10 mm	10 mm	10 mm
temperature range	-20~+60 °C	-20~+60 °C	-20~+60 °C	-20~+60 °C	-20~+60 °C
influence protection	IP66	IP66	IP66	IP66	IP66
output	4Pin SOCKET	4Pin SOCKET	4Pin SOCKET	4Pin SOCKET	4Pin SOCKET
output stage	PNP TRANSISTOR	PNP TRANSISTOR	PNP TRANSISTOR	PNP TRANSISTOR	PNP TRANSISTOR
output function	NC	NC	NC	NO	NO
voltage range	10-30VDC	10-60VDC	10-60VDC	10-30VDC	10-60VDC
max output current	250 mA	450 mA	250 mA	250 mA	450 mA
max output frequency	300 Hz	300 Hz	300 Hz	300 Hz	300 Hz
indicator led	yes	yes	yes	yes	yes
max drop voltage	2 V	2 V	2 V	2 V	2 V
max noload or leakage current	15 mA	15 mA	15 mA	15 mA	15 mA
pressure rate	3 bar	3 bar	3 bar	3 bar	3 bar
mounting	flush(shielded)	flush(shielded)	flush(shielded)	flush(shielded)	flush(shielded)
revers voltage protection	yes	yes	yes	yes	yes
short circuit protection	yes	yes	yes	yes	yes
pick voltage protection	yes	yes	yes	yes	yes
circuit					

Central office : No 36 , karimkhan ave. , darvazeh tehran , tabriz , iran ; zip code : 5157913399 ; P.O. box : 51575-5140
 Email : info@tabrizpeguh.com ; Website : www.tabrizpeguh.com ; Tel : +984133330490 ; Fax : +984133318200

3wire DC 4pin connector PNP inductive sensor

housing					
	M30X1.5Ni PLATED Brass	M30X1.5Ni PLATED Brass	M30X1.5Ni PLATED Brass	M30X1.5Ni PLATED Brass	M30X1.5Ni PLATED Brass
code	IPS-310-OP-30-V-S4	IPS-315-CP-30-S4	IPS-315-CP-30-VI-S4	IPS-315-CP-30-V-S4	IPS-315-OP-30-S4
number of wires	3	3	3	3	3
switching distance	10 mm	15 mm	15 mm	15 mm	15 mm
temperature range	-20~+60 °C	-20~+60 °C	-20~+60 °C	-20~+60 °C	-20~+60 °C
influence protection	IP66	IP66	IP66	IP66	IP66
output	4Pin SOCKET	4Pin SOCKET	4Pin SOCKET	4Pin SOCKET	4Pin SOCKET
output stage	PNP TRANSISTOR	PNP TRANSISTOR	PNP TRANSISTOR	PNP TRANSISTOR	PNP TRANSISTOR
output function	NO	NC	NC	NC	NO
voltage range	10-60VDC	10-30VDC	10-60VDC	10-60VDC	10-30VDC
max output current	250 mA	250 mA	450 mA	250 mA	250 mA
max output frequency	300 Hz	300 Hz	300 Hz	300 Hz	300 Hz
indicator led	yes	yes	yes	yes	yes
max drop voltage	2 V	2 V	2 V	2 V	2 V
max no-load or leakage current	15 mA	15 mA	15 mA	15 mA	15 mA
pressure rate	3 bar	3 bar	3 bar	3 bar	3 bar
mounting	flush(shielded)	non flush (unshielded)	non flush (unshielded)	non flush (unshielded)	non flush (unshielded)
revers voltage protection	yes	yes	yes	yes	yes
short circuit protection	yes	yes	yes	yes	yes
pick voltage protection	yes	yes	yes	yes	yes
circuit					

3wire DC 4pin connector PNP inductive sensor

housing					
	M30X1.5Ni PLATED Brass	M30X1.5Ni PLATED Brass	M34X1.5Ni PLATED Brass	M34X1.5Ni PLATED Brass	M34X1.5Ni PLATED Brass
code	IPS-315-OP-30-VI-S4	IPS-315-OP-30-V-S4	IPS-315-CP-34-S4	IPS-315-CP-34-VI-S4	IPS-315-CP-34-V-S4
number of wires	3	3	3	3	3
switching distance	15 mm	15 mm	15 mm	15 mm	15 mm
temperature range	-20~+60 °C	-20~+60 °C	-20~+60 °C	-20~+60 °C	-20~+60 °C
influence protection	IP66	IP66	IP66	IP66	IP66
output	4Pin SOCKET	4Pin SOCKET	4Pin SOCKET	4Pin SOCKET	4Pin SOCKET
output stage	PNP TRANSISTOR	PNP TRANSISTOR	PNP TRANSISTOR	PNP TRANSISTOR	PNP TRANSISTOR
output function	NO	NO	NC	NC	NC
voltage range	10-60VDC	10-60VDC	10-30VDC	10-60VDC	10-60VDC
max output current	450 mA	250 mA	250 mA	450 mA	250 mA
max output frequency	300 Hz	300 Hz	300 Hz	300 Hz	300 Hz
indicator led	yes	yes	yes	yes	yes
max drop voltage	2 V	2 V	2 V	2 V	2 V
max no-load or leakage current	15 mA	15 mA	15 mA	15 mA	15 mA
pressure rate	3 bar	3 bar	3 bar	3 bar	3 bar
mounting	non flush (unshielded)	non flush (unshielded)	flush(shielded)	flush(shielded)	flush(shielded)
revers voltage protection	yes	yes	yes	yes	yes
short circuit protection	yes	yes	yes	yes	yes
pick voltage protection	yes	yes	yes	yes	yes
circuit					

Central office : No 36 , karimkhan ave. , darvazeh tehran , tabriz , iran ; zip code : 5157913399 ; P.O. box : 51575-5140
 Email : info@tabrizpeguh.com ; Website : www.tabrizpeguh.com ; Tel : +984133330490 ; Fax : +984133318200











3wire DC 4pin connector PNP inductive sensor

housing					
	M34X1.5Ni PLATED Brass	M34X1.5Ni PLATED Brass	M34X1.5Ni PLATED Brass	M34X1.5Ni PLATED Brass	M34X1.5Ni PLATED Brass
code	IPS-315-OP-34-S4	IPS-315-OP-34-VI-S4	IPS-315-OP-34-V-S4	IPS-320-CP-34-S4	IPS-320-CP-34-VI-S4
number of wires	3	3	3	3	3
switching distance	15 mm	15 mm	15 mm	20 mm	20 mm
temperature range	-20~+60 °C	-20~+60 °C	-20~+60 °C	-20~+60 °C	-20~+60 °C
influence protection	IP66	IP66	IP66	IP66	IP66
output	4Pin SOCKET	4Pin SOCKET	4Pin SOCKET	4Pin SOCKET	4Pin SOCKET
output stage	PNP TRANSISTOR	PNP TRANSISTOR	PNP TRANSISTOR	PNP TRANSISTOR	PNP TRANSISTOR
output function	NO	NO	NO	NC	NC
voltage range	10-30VDC	10-60VDC	10-60VDC	10-30VDC	10-60VDC
max output current	250 mA	450 mA	250 mA	250 mA	450 mA
max output frequency	300 Hz	300 Hz	300 Hz	300 Hz	300 Hz
indicator led	yes	yes	yes	yes	yes
max drop voltage	2 V	2 V	2 V	2 V	2 V
max no-load or leakage current	15 mA	15 mA	15 mA	15 mA	15 mA
pressure rate	3 bar	3 bar	3 bar	3 bar	3 bar
mounting	flush(shielded)	flush(shielded)	flush(shielded)	non flush (unshielded)	non flush (unshielded)
reverse voltage protection	yes	yes	yes	yes	yes
short circuit protection	yes	yes	yes	yes	yes
pick voltage protection	yes	yes	yes	yes	yes
circuit					

3wire DC 4pin connector PNP inductive sensor

housing					
	M34X1.5Ni PLATED Brass	M34X1.5Ni PLATED Brass	M34X1.5Ni PLATED Brass	M34X1.5Ni PLATED Brass	M40X1.5Ni PLATED Brass
code	IPS-320-CP-34-V-S4	IPS-320-OP-34-S4	IPS-320-OP-34-VI-S4	IPS-320-OP-34-V-S4	IPS-320-CP-40-S4
number of wires	3	3	3	3	3
switching distance	20 mm	20 mm	20 mm	20 mm	20 mm
temperature range	-20~+60 °C	-20~+60 °C	-20~+60 °C	-20~+60 °C	-20~+60 °C
influence protection	IP66	IP66	IP66	IP66	IP66
output	4Pin SOCKET	4Pin SOCKET	4Pin SOCKET	4Pin SOCKET	4Pin SOCKET
output stage	PNP TRANSISTOR	PNP TRANSISTOR	PNP TRANSISTOR	PNP TRANSISTOR	PNP TRANSISTOR
output function	NC	NO	NO	NO	NC
voltage range	10-60VDC	10-30VDC	10-60VDC	10-60VDC	10-30VDC
max output current	250 mA	250 mA	450 mA	250 mA	250 mA
max output frequency	300 Hz	300 Hz	300 Hz	300 Hz	300 Hz
indicator led	yes	yes	yes	yes	yes
max drop voltage	2 V	2 V	2 V	2 V	2 V
max no-load or leakage current	15 mA	15 mA	15 mA	15 mA	15 mA
pressure rate	3 bar	3 bar	3 bar	3 bar	3 bar
mounting	non flush (unshielded)	non flush (unshielded)	non flush (unshielded)	non flush (unshielded)	flush(shielded)
revers voltage protection	yes	yes	yes	yes	yes
short circuit protection	yes	yes	yes	yes	yes
pick voltage protection	yes	yes	yes	yes	yes
circuit					

3wire DC 4pin connector PNP inductive sensor











housing					
	M40X1.5Ni PLATED Brass	M40X1.5Ni PLATED Brass	M40X1.5Ni PLATED Brass	M40X1.5Ni PLATED Brass	M40X1.5Ni PLATED Brass
code	IPS-320-CP-40-VI-S4	IPS-320-CP-40-V-S4	IPS-320-OP-40-S4	IPS-320-OP-40-VI-S4	IPS-320-OP-40-V-S4
number of wires	3	3	3	3	3
switching distance	20 mm	20 mm	20 mm	20 mm	20 mm
temperature range	-20~+60 °C	-20~+60 °C	-20~+60 °C	-20~+60 °C	-20~+60 °C
influence protection	IP66	IP66	IP66	IP66	IP66
output	4Pin SOCKET	4Pin SOCKET	4Pin SOCKET	4Pin SOCKET	4Pin SOCKET
output stage	PNP TRANSISTOR	PNP TRANSISTOR	PNP TRANSISTOR	PNP TRANSISTOR	PNP TRANSISTOR
output function	NC	NC	NO	NO	NO
voltage range	10-60VDC	10-60VDC	10-30VDC	10-60VDC	10-60VDC
max output current	450 mA	250 mA	250 mA	450 mA	250 mA
max output frequency	300 Hz	300 Hz	300 Hz	300 Hz	300 Hz
indicator led	yes	yes	yes	yes	yes
max drop voltage	2 V	2 V	2 V	2 V	2 V
max no-load or leakage current	15 mA	15 mA	15 mA	15 mA	15 mA
pressure rate	3 bar	3 bar	3 bar	3 bar	3 bar
mounting	flush(shielded)	flush(shielded)	flush(shielded)	flush(shielded)	flush(shielded)
revers voltage protection	yes	yes	yes	yes	yes
short circuit protection	yes	yes	yes	yes	yes
pick voltage protection	yes	yes	yes	yes	yes
circuit					

3wire DC 4pin connector PNP inductive sensor

housing					
	22mm dia. PA or PP	22mm dia. PA or PP	22mm dia. PA or PP	22mm dia. PA or PP	22mm dia. PA or PP
code	IPS-310-CP-P22-S4	IPS-310-CP-P22-VI-S4	IPS-310-CP-P22-V-S4	IPS-310-OP-P22-S4	IPS-310-OP-P22-VI-S4
number of wires	3	3	3	3	3
switching distance	10 mm	10 mm	10 mm	10 mm	10 mm
temperature range	-20~+60 °C	-20~+60 °C	-20~+60 °C	-20~+60 °C	-20~+60 °C
influence protection	IP66	IP66	IP66	IP66	IP66
output	4Pin SOCKET	4Pin SOCKET	4Pin SOCKET	4Pin SOCKET	4Pin SOCKET
output stage	PNP TRANSISTOR	PNP TRANSISTOR	PNP TRANSISTOR	PNP TRANSISTOR	PNP TRANSISTOR
output function	NC	NC	NC	NO	NO
voltage range	10-30VDC	10-60VDC	10-60VDC	10-30VDC	10-60VDC
max output current	250 mA	450 mA	250 mA	250 mA	450 mA
max output frequency	500 Hz	500 Hz	500 Hz	500 Hz	500 Hz
indicator led	yes	yes	yes	yes	yes
max drop voltage	2 V	2 V	2 V	2 V	2 V
max no-load or leakage current	15 mA	15 mA	15 mA	15 mA	15 mA
pressure rate	3 bar	3 bar	3 bar	3 bar	3 bar
mounting	non flush (unshielded)	non flush (unshielded)	non flush (unshielded)	non flush (unshielded)	non flush (unshielded)
revers voltage protection	yes	yes	yes	yes	yes
short circuit protection	yes	yes	yes	yes	yes
pick voltage protection	yes	yes	yes	yes	yes
circuit					

Central office : No 36 , karimkhan ave. , darvazeh tehran , tabriz , iran ; zip code : 5157913399 ; P.O. box : 51575-5140
 Email : info@tabrizpeguh.com ; Website : www.tabrizpeguh.com ; Tel : +984133330490 ; Fax : +984133318200

3wire DC 4pin connector PNP inductive sensor

housing					
	22mm dia. PA or PP	34mm dia. PA or PP	34mm dia. PA or PP	34mm dia. PA or PP	34mm dia. PA or PP
code	IPS-310-OP-P22-V-S4	IPS-320-CP-P34-S4	IPS-320-CP-P34-VI-S4	IPS-320-CP-P34-V-S4	IPS-320-OP-P34-S4
number of wires	3	3	3	3	3
switching distance	10 mm	20 mm	20 mm	20 mm	20 mm
temperature range	-20~+60 °C	-20~+60 °C	-20~+60 °C	-20~+60 °C	-20~+60 °C
influence protection	IP66	IP66	IP66	IP66	IP66
output	4Pin SOCKET	4Pin SOCKET	4Pin SOCKET	4Pin SOCKET	4Pin SOCKET
output stage	PNP TRANSISTOR	PNP TRANSISTOR	PNP TRANSISTOR	PNP TRANSISTOR	PNP TRANSISTOR
output function	NO	NC	NC	NC	NO
voltage range	10-60VDC	10-30VDC	10-60VDC	10-60VDC	10-30VDC
max output current	250 mA	250 mA	450 mA	250 mA	250 mA
max output frequency	500 Hz	300 Hz	300 Hz	300 Hz	300 Hz
indicator led	yes	yes	yes	yes	yes
max drop voltage	2 V	2 V	2 V	2 V	2 V
max no-load or leakage current	15 mA	15 mA	15 mA	15 mA	15 mA
pressure rate	3 bar	3 bar	3 bar	3 bar	3 bar
mounting	non flush (unshielded)	non flush (unshielded)	non flush (unshielded)	non flush (unshielded)	non flush (unshielded)
revers voltage protection	yes	yes	yes	yes	yes
short circuit protection	yes	yes	yes	yes	yes
pick voltage protection	yes	yes	yes	yes	yes
circuit					







Central office : No 36 , karimkhan ave. , darvazeh tehran , tabriz , iran ; zip code : 5157913399 ; P.O. box : 51575-5140
 Email : info@tabrizpeguh.com ; Website : www.tabrizpeguh.com ; Tel : +984133330490 ; Fax : +984133318200

3wire DC 4pin connector PNP inductive sensor

housing					
	34mm dia. PA or PP	34mm dia. PA or PP	REC. 40X40X113 PA or PP	REC. 40X40X113 PA or PP	REC. 40X40X113 PA or PP
code	IPS-320-OP-P34-VI-S4	IPS-320-OP-P34-V-S4	IPS-320-CP-R40-T	IPS-320-CP-R40-VI-T	IPS-320-CP-R40-V-T
number of wires	3	3	3	3	3
switching distance	20 mm	20 mm	20 mm	20 mm	20 mm
temperature range	-20~+60 °C	-20~+60 °C	-20~+60 °C	-20~+60 °C	-20~+60 °C
influence protection	IP66	IP66	IP66	IP66	IP66
output	4Pin SOCKET	4Pin SOCKET	TERMINAL	TERMINAL	TERMINAL
output stage	PNP TRANSISTOR	PNP TRANSISTOR	PNP TRANSISTOR	PNP TRANSISTOR	PNP TRANSISTOR
output function	NO	NO	NC	NC	NC
voltage range	10-60VDC	10-60VDC	10-30VDC	10-60VDC	10-60VDC
max output current	450 mA	250 mA	250 mA	450 mA	250 mA
max output frequency	300 Hz	300 Hz	300 Hz	300 Hz	300 Hz
indicator led	yes	yes	yes	yes	yes
max drop voltage	2 V	2 V	2 V	2 V	2 V
max no-load or leakage current	15 mA	15 mA	15 mA	15 mA	15 mA
pressure rate	3 bar	3 bar	3 bar	3 bar	3 bar
mounting	non flush (unshielded)	non flush (unshielded)	non flush (unshielded)	non flush (unshielded)	non flush (unshielded)
revers voltage protection	yes	yes	yes	yes	yes
short circuit protection	yes	yes	yes	yes	yes
pick voltage protection	yes	yes	yes	yes	yes
circuit					

Central office : No 36 , karimkhan ave. , darvazeh tehran , tabriz , iran ; zip code : 5157913399 ; P.O. box : 51575-5140
 Email : info@tabrizpeguh.com ; Website : www.tabrizpeguh.com ; Tel : +984133330490 ; Fax : +984133318200

3wire DC 4pin connector PNP inductive sensor

housing					
	REC. 40X40X113 PA or PP	REC. 40X40X113 PA or PP	REC. 40X40X113 PA or PP		
code	IPS-320-OP-R40-T	IPS-320-OP-R40-VI-T	IPS-320-OP-R40-V-T		
number of wires	3	3	3		
switching distance	20 mm	20 mm	20 mm		
temperature range	-20~+60 °C	-20~+60 °C	-20~+60 °C		
influence protection	IP66	IP66	IP66		
output	TERMINAL	TERMINAL	TERMINAL		
output stage	PNP TRANSISTOR	PNP TRANSISTOR	PNP TRANSISTOR		
output function	NO	NO	NO		
voltage range	10-30VDC	10-60VDC	10-60VDC		
max output current	250 mA	450 mA	250 mA		
max output frequency	300 Hz	300 Hz	300 Hz		
indicator led	yes	yes	yes		
max drop voltage	2 V	2 V	2 V		
max no-load or leakage current	15 mA	15 mA	15 mA		
pressure rate	3 bar	3 bar	3 bar		
mounting	non flush (unshielded)	non flush (unshielded)	non flush (unshielded)		
revers voltage protection	yes	yes	yes		
short circuit protection	yes	yes	yes		
pick voltage protection	yes	yes	yes		
circuit					

Central office : No 36 , karimkhan ave. , darvazeh tehran , tabriz , iran ; zip code : 5157913399 ; P.O. box : 51575-5140
 Email : info@tabrizpeguh.com ; Website : www.tabrizpeguh.com ; Tel : +984133330490 ; Fax : +984133318200