





















continuous pre cabled Inductive Sensor

housing					
	M12X1Ni PLATED Brass	M12X1Ni PLATED Brass	M14X1Ni PLATED Brass	M14X1Ni PLATED Brass	M18X1Ni PLATED Brass
code	IPS-302-AV-12-P	IPS-304-AV-12-P	IPS-303-AV-14-P	IPS-305-AV-14-P	IPS-305-AI-18-P
number of wires	3	3	3	3	3
output type	0-10V	0-10V	0-10V	0-10V	4-20mA
switching distance	2 mm	4 mm	3 mm	5 mm	5 mm
temperature range	-20~+60 °C	-20~+60 °C	-20~+60 °C	-20~+60 °C	-20~+60 °C
influence protection	IP66	IP66	IP66	IP66	IP66
output	CABLE3X0.25-1.5m	CABLE3X0.25-1.5m	CABLE3X0.25-1.5m	CABLE3X0.25-1.5m	CABLE3X0.25-1.5m
output stage	TRANSISTOR	TRANSISTOR	TRANSISTOR	TRANSISTOR	TRANSISTOR
output function	ANALOG	ANALOG	ANALOG	ANALOG	ANALOG
voltage range	15-30 VDC	15-30 VDC	15-30 VDC	15-30 VDC	15-30 VDC
mounting	flush(shielded)	non flush (unshielded)	flush(shielded)	non flush (unshielded)	flush(shielded)
circuit					











continuous pre cabled Inductive Sensor

housing					
	M18X1Ni PLATED Brass	M18X1Ni PLATED Brass	M18X1Ni PLATED Brass	M18X1Ni PLATED Brass	M18X1Ni PLATED Brass
code	IPS-305-AV-18-N	IPS-305-AV-18-P	IPS-305-AI-18-N	IPS-308-AV-18-N	IPS-308-AV-18-P
number of wires	3	3	3	3	3
output type	10-0V	0-10V	20-4mA	10-0V	0-10V
switching distance	5 mm	5 mm	8 mm	8 mm	8 mm
temperature range	-20~+60 °C	-20~+60 °C	-20~+60 °C	-20~+60 °C	-20~+60 °C
influence protection	IP66	IP66	IP66	IP66	IP66
output	CABLE3X0.25-1.5m	CABLE3X0.25-1.5m	CABLE3X0.25-1.5m	CABLE3X0.25-1.5m	CABLE3X0.25-1.5m
output stage	TRANSISTOR	TRANSISTOR	TRANSISTOR	TRANSISTOR	TRANSISTOR
output function	ANALOG	ANALOG	ANALOG	ANALOG	ANALOG
voltage range	15-30 VDC	15-30 VDC	15-30 VDC	15-30 VDC	15-30 VDC
mounting	flush(shielded)	flush(shielded)	non flush (unshielded)	non flush (unshielded)	non flush (unshielded)
circuit					

continuous pre cabled Inductive Sensor

housing					
	M18X1Ni PLATED Brass	M18X1Ni PLATED Brass	M22X1.5Ni PLATED Brass	M22X1.5Ni PLATED Brass	M22X1.5Ni PLATED Brass
code	IPS-308-AI-18-P	IPS-308-AI-18-N	IPS-308-AI-22-P	IPS-308-AV-22-N	IPS-308-AV-22-P
number of wires	3	3	3	3	3
output type	4-20mA	20-4mA	4-20mA	10-0V	0-10V
switching distance	8 mm	8 mm	8 mm	8 mm	8 mm
temperature range	-20~+60 °C	-20~+60 °C	-20~+60 °C	-20~+60 °C	-20~+60 °C
influence protection	IP66	IP66	IP66	IP66	IP66
output	CABLE3X0.25-1.5m	CABLE3X0.25-1.5m	CABLE3X0.25-1.5m	CABLE3X0.25-1.5m	CABLE3X0.25-1.5m
output stage	TRANSISTOR	TRANSISTOR	TRANSISTOR	TRANSISTOR	TRANSISTOR
output function	ANALOG	ANALOG	ANALOG	ANALOG	ANALOG
voltage range	15-30 VDC	15-30 VDC	15-30 VDC	15-30 VDC	15-30 VDC
mounting	non flush (unshielded)	non flush (unshielded)	flush(shielded)	flush(shielded)	flush(shielded)
circuit					











continuous pre cabled Inductive Sensor

housing					
	M22X1.5Ni PLATED Brass	M22X1.5Ni PLATED Brass	M22X1.5Ni PLATED Brass	M22X1.5Ni PLATED Brass	M22X1.5Ni PLATED Brass
code	IPS-308-AI-22-N	IPS-310-AI-22-P	IPS-310-AV-22-N	IPS-310-AV-22-P	IPS-310-AI-22-N
number of wires	3	3	3	3	3
output type	20-4mA	4-20mA	10-0V	0-10V	20-4mA
switching distance	8 mm	10 mm	10 mm	10 mm	10 mm
temperature range	-20~+60 °C	-20~+60 °C	-20~+60 °C	-20~+60 °C	-20~+60 °C
influence protection	IP66	IP66	IP66	IP66	IP66
output	CABLE3X0.25-1.5m	4Pin SOCKET	CABLE3X0.25-1.5m	CABLE3X0.25-1.5m	CABLE3X0.25-1.5m
output stage	TRANSISTOR	TRANSISTOR	TRANSISTOR	TRANSISTOR	TRANSISTOR
output function	ANALOG	ANALOG	ANALOG	ANALOG	ANALOG
voltage range	15-30 VDC	15-30 VDC	15-30 VDC	15-30 VDC	15-30 VDC
mounting	flush(shielded)	non flush (unshielded)	non flush (unshielded)	non flush (unshielded)	non flush (unshielded)
circuit					

continuous pre cabled Inductive Sensor

housing					
	M30X1.5Ni PLATED Brass	M30X1.5Ni PLATED Brass	M30X1.5Ni PLATED Brass	M30X1.5Ni PLATED Brass	M30X1.5Ni PLATED Brass
code	IPS-310-AI-30-N	IPS-310-AI-30-P	IPS-310-AV-30-N	IPS-310-AV-30-P	IPS-315-AI-30-N
number of wires	3	3	3	3	3
output type	20-4mA	4-20mA	10-0V	0-10V	20-4mA
switching distance	10 mm	10 mm	10 mm	10 mm	15 mm
temperature range	-20~+60 °C	-20~+60 °C	-20~+60 °C	-20~+60 °C	-20~+60 °C
influence protection	IP66	IP66	IP66	IP66	IP66
output	CABLE3X0.25-1.5m	CABLE3X0.25-1.5m	CABLE3X0.25-1.5m	CABLE3X0.25-1.5m	CABLE3X0.25-1.5m
output stage	TRANSISTOR	TRANSISTOR	TRANSISTOR	TRANSISTOR	TRANSISTOR
output function	ANALOG	ANALOG	ANALOG	ANALOG	ANALOG
voltage range	15-30 VDC	15-30 VDC	15-30 VDC	15-30 VDC	15-30 VDC
mounting	flush(shielded)	flush(shielded)	flush(shielded)	flush(shielded)	non flush (unshielded)
circuit					

continuous pre cabled Inductive Sensor

housing					
	M30X1.5Ni PLATED Brass	M30X1.5Ni PLATED Brass	M30X1.5Ni PLATED Brass	M34X1.5Ni PLATED Brass	M34X1.5Ni PLATED Brass
code	IPS-315-AI-30-P	IPS-315-AV-30-N	IPS-315-AV-30-P	IPS-315-AI-34-N	IPS-315-AI-34-P
number of wires	3	3	3	3	3
output type	4-20mA	10-0V	0-10V	20-4mA	4-20mA
switching distance	15 mm	15 mm	15 mm	15 mm	15 mm
temperature range	-20~+60 °C	-20~+60 °C	-20~+60 °C	-20~+60 °C	-20~+60 °C
influence protection	IP66	IP66	IP66	IP66	IP66
output	CABLE3X0.25-1.5m	CABLE3X0.25-1.5m	CABLE3X0.25-1.5m	CABLE3X0.25-1.5m	CABLE3X0.25-1.5m
output stage	TRANSISTOR	TRANSISTOR	TRANSISTOR	TRANSISTOR	TRANSISTOR
output function	ANALOG	ANALOG	ANALOG	ANALOG	ANALOG
voltage range	15-30 VDC	15-30 VDC	15-30 VDC	15-30 VDC	15-30 VDC
mounting	non flush (unshielded)	non flush (unshielded)	non flush (unshielded)	flush(shielded)	flush(shielded)
circuit					

continuous pre cabled Inductive Sensor

housing					
	M34X1.5Ni PLATED Brass	M34X1.5Ni PLATED Brass	M34X1.5Ni PLATED Brass	M34X1.5Ni PLATED Brass	M34X1.5Ni PLATED Brass
code	IPS-315-AV-34-N	IPS-315-AV-34-P	IPS-320-AI-34-N	IPS-320-AI-34-P	IPS-320-AV-34-N
number of wires	3	3	3	3	3
output type	10-0V	0-10V	20-4mA	4-20mA	10-0V
switching distance	15 mm	15 mm	20 mm	20 mm	20 mm
temperature range	-20~+60 °C	-20~+60 °C	-20~+60 °C	-20~+60 °C	-20~+60 °C
influence protection	IP66	IP66	IP66	IP66	IP66
output	CABLE3X0.25-1.5m	CABLE3X0.25-1.5m	CABLE3X0.25-1.5m	CABLE3X0.25-1.5m	CABLE3X0.25-1.5m
output stage	TRANSISTOR	TRANSISTOR	TRANSISTOR	TRANSISTOR	TRANSISTOR
output function	ANALOG	ANALOG	ANALOG	ANALOG	ANALOG
voltage range	15-30 VDC	15-30 VDC	15-30 VDC	15-30 VDC	15-30 VDC
mounting	flush(shielded)	flush(shielded)	non flush (unshielded)	non flush (unshielded)	non flush (unshielded)
circuit					

Central office : No 36 , karimkhan ave. , darvazeh tehran , tabriz , iran ; zip code : 5157913399 ; P.O. box : 51575-5140  
 Email : [info@tabrizpeguh.com](mailto:info@tabrizpeguh.com) ; Website : [www.tabrizpeguh.com](http://www.tabrizpeguh.com) ; Tel : +984133330490 ; Fax : +984133318200

continuous pre cabled Inductive Sensor

housing					
	M34X1.5Ni PLATED Brass	REC. 40X40X113 PA or PP	REC. 40X40X113 PA or PP	REC. 40X40X113 PA or PP	REC. 40X40X113 PA or PP
code	IPS-320-AV-34-P	IPS-320-AV-R40-N	IPS-320-AV-R40-P	IPS-320-AI-R40-N	IPS-320-AI-R40-P
number of wires	3	3	3	3	3
output type	0-10V	10-0V	0-10V	20-4mA	4-20mA
switching distance	20 mm	20 mm	20 mm	20 mm	20 mm
temperature range	-20~+60 °C	-20~+60 °C	-20~+60 °C	-20~+60 °C	-20~+60 °C
influence protection	IP66	IP66	IP66	IP66	IP66
output	CABLE3X0.25-1.5m	CABLE3X0.25-1.5m	CABLE3X0.25-1.5m	CABLE3X0.25-1.5m	CABLE3X0.25-1.5m
output stage	TRANSISTOR	TRANSISTOR	TRANSISTOR	TRANSISTOR	TRANSISTOR
output function	ANALOG	ANALOG	ANALOG	ANALOG	ANALOG
voltage range	15-30 VDC	15-30 VDC	15-30 VDC	15-30 VDC	15-30 VDC
mounting	non flush (unshielded)	non flush (unshielded)	non flush (unshielded)	non flush (unshielded)	non flush (unshielded)
circuit					