












pre cabled capacitive two-wire AC sensors

housing					
	M30X1.5Ni PLATED brass	M30X1.5Ni PLATED brass	M30X1.5Ni PLATED brass	M30X1.5Ni PLATED brass	M18X1Ni PLATED brass
code	CPS-210-CA-30	CPS-210-OA-30	CPS-220-CA-30	CPS-220-OA-30	CPS-210-OA-18
number of wires	2	2	2	2	2
switching distance	10 mm	10 mm	20 mm	20 mm	10 mm
temperature range	-20~+60 °C	-20~+60 °C	-20~+60 °C	-20~+60 °C	-20~+60 °C
influence protection	IP 66	IP 66	IP 66	IP 66	IP 66
output stage	THYRISTOR	THYRISTOR	THYRISTOR	THYRISTOR	THYRISTOR
output function	NC	NO	NC	NO	NO
voltage range	20-250VAC	20-250VAC	20-250VAC	20-250VAC	20-250VAC
max output current	250 mA	250 mA	250 mA	250 mA	250 mA
max output ferequence	2 Hz	2 Hz	2 Hz	2 Hz	2 Hz
indicator led	yes	yes	yes	yes	yes
max drop voltage	10 V	10 V	10 V	10 V	10 V
max no-load or leakage current	3 mA	3 mA	3 mA	3 mA	3 mA
revers voltage protection	no	no	no	no	no
short circuit protection	no	no	no	no	no
output	CABLE2X0.5-1.5m	CABLE2X0.5-1.5m	CABLE2X0.5-1.5m	CABLE2X0.5-1.5m	CABLE2X0.5-1.5m
mounting	flush(shielded)	flush(shielded)	non flush (unshielded)	non flush (unshielded)	non flush (unshielded)
circuit					

Central office : No 36 , karimkhan ave. , darvazeh tehran , tabriz , iran ; zip code : 5157913399 ; P.O. box : 51575-5140  
 Email : [info@tabrizpeguh.com](mailto:info@tabrizpeguh.com) ; Website : [www.tabrizpeguh.com](http://www.tabrizpeguh.com) ; Tel : +984133330490 ; Fax : +984133318200

pre cabled capacitive two-wire AC sensors

housing					
	M18X1Ni PLATED brass				
code	CPS-210-CA-18				
number of wires	2				
switching distance	10 mm				
temperature range	-20~+60 °C				
influence protection	IP 66				
output stage	THYRISTOR				
output function	NC				
voltage range	20-250VAC				
max output current	250 mA				
indicator led	yes				
max drop voltage	10 V				
revers voltage protection	no				
short circuit protection	no				
output	CABLE2X0.5-1.5m				
mounting	non flush (unshielded)				
circuit	