

4pin connector capacitive two-wire AC sensors

housing					
	M30X1.5Ni PLATED brass	M30X1.5Ni PLATED brass	M30X1.5Ni PLATED brass	M30X1.5Ni PLATED brass	
code	CPS-210-CA-30-S4	CPS-210-OA-30-S4	CPS-220-CA-30-S4	CPS-220-OA-30-S4	
number of wires	2	2	2	2	
switching distance	10 mm	10 mm	20 mm	20 mm	
temperature range	-20~+60 °C	-20~+60 °C	-20~+60 °C	-20~+60 °C	
influence protection	IP 66	IP 66	IP 66	IP 66	
output stage	THYRISTOR	THYRISTOR	THYRISTOR	THYRISTOR	
output function	NC	NO	NC	NO	
voltage range	20-250VAC	20-250VAC	20-250VAC	20-250VAC	
max output current	250 mA	250 mA	250 mA	250 mA	
max output frequency	2 Hz	2 Hz	2 Hz	2 Hz	
indicator led	yes	yes	yes	yes	
max drop voltage	10 V	10 V	10 V	10 V	
max no-load or leakage current	3 mA	3 mA	3 mA	3 mA	
reverse voltage protection	no	no	no	no	
short circuit protection	no	no	no	no	
output	4Pin SOCKET	4Pin SOCKET	4Pin SOCKET	4Pin SOCKET	
mounting	flush(shielded)	flush(shielded)	non flush (unshielded)	non flush (unshielded)	
pick voltage protection	yes	yes	yes	yes	
circuit					

Central office : No 36 , karimkhan ave. , darvazeh tehran , tabriz , iran ; zip code : 5157913399 ; P.O. box : 51575-5140  
 Email : [info@tabrizpeguh.com](mailto:info@tabrizpeguh.com) ; Website : [www.tabrizpeguh.com](http://www.tabrizpeguh.com) ; Tel : +984133330490 ; Fax : +984133318200