











pre cabled retro-reflective optoelectronic sensors

housing					
	M30X1.5 Ni PLATED Brass	M30X1.5 Ni PLATED Brass	M30X1.5 Ni PLATED Brass	M30X1.5 Ni PLATED Brass	REC. 50X75X30 PA or PP
code	OPS-3150-CN-30-RR	OPS-3150-CP-30-RR	OPS-3150-ON-30-RR	OPS-3150-OP-30-RR	OPS-3400-CN-R50-RR
number of wires	3	3	3	3	3
output stage	NPN TRANSISTOR	PNP TRANSISTOR	NPN TRANSISTOR	PNP TRANSISTOR	NPN TRANSISTOR
output function	NC	NC	NO	NO	NC
switching distance	150 cm	150 cm	150 cm	150 cm	400 cm
voltage range	10-30VDC	10-30VDC	10-30VDC	10-30VDC	10-30VDC
max output current	250 mA	250 mA	250 mA	250 mA	250 mA
temperature range	-20~+60 °C	-20~+60 °C	-20~+60 °C	-20~+60 °C	-20~+60 °C
max output frequency	500 Hz	500 Hz	500 Hz	500 Hz	500 Hz
indicator led	yes	yes	yes	yes	yes
max drop voltage	2 V	2 V	2 V	2 V	2 V
influence protection	IP66	IP66	IP66	IP66	IP66
revers voltage protection	yes	yes	yes	yes	yes
short circuit protection	no	no	no	no	no
output	CABLE3X0.35-1.5m	CABLE3X0.35-1.5m	CABLE3X0.35-1.5m	CABLE3X0.35-1.5m	CABLE3X0.35-1.5m
circuit					

Central office : No 36 , karimkhan ave. , darvazeh tehran , tabriz , iran ; zip code : 5157913399 ; P.O. box : 51575-5140
 Email : info@tabrizpeguh.com ; Website : www.tabrizpeguh.com ; Tel : +984133330490 ; Fax : +984133318200

pre cabled retro-reflective optoelectronic sensors

housing					
	REC. 50X75X30 PA or PP	REC. 50X75X30 PA or PP	REC. 50X75X30 PA or PP	REC. 50X75X30 PA or PP	REC. 50X75X30 PA or PP
code	OPS-3400-CP-R50-RR	OPS-3400-ON-R50-RR	OPS-3400-OP-R50-RR	OPS-4400-CA-R50-RR	OPS-4400-OA-R50-RR
number of wires	3	3	3	4	4
output stage	PNP TRANSISTOR	NPN TRANSISTOR	PNP TRANSISTOR	RELAY	RELAY
output function	NC	NO	NO	NC	NO
switching distance	400 cm	400 cm	400 cm	400 cm	400 cm
voltage range	10-30VDC	10-30VDC	10-30VDC	220VAC	220VAC
max output current	250 mA	250 mA	250 mA	250 mA	250 mA
temperature range	-20~+60 °C	-20~+60 °C	-20~+60 °C	-20~+60 °C	-20~+60 °C
max output frequency	500 Hz	500 Hz	500 Hz	10 Hz	10 Hz
indicator led	yes	yes	yes	yes	yes
max drop voltage	2 V	2 V	2 V	2 V	2 V
influence protection	IP66	IP66	IP66	IP66	IP66
revers voltage protection	yes	yes	yes	yes	yes
short circuit protection	no	no	no	no	no
output	CABLE3X0.35-1.5m	CABLE3X0.35-1.5m	CABLE3X0.35-1.5m	CABLE4X0.35-1.5m	CABLE4X0.35-1.5m
circuit					

Central office : No 36 , karimkhan ave. , darvazeh tehran , tabriz , iran ; zip code : 5157913399 ; P.O. box : 51575-5140
 Email : info@tabrizpeguh.com ; Website : www.tabrizpeguh.com ; Tel : +984133330490 ; Fax : +984133318200