









4pin connector retro-reflective optoelectronic sensors

| | | | | | |
|---------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|--|
| housing |  |  |  |  | |
| | M30X1.5 Ni PLATED Brass | M30X1.5 Ni PLATED Brass | M30X1.5 Ni PLATED Brass | M30X1.5 Ni PLATED Brass | |
| code | OPS-3150-CN-30-RR-S4 | OPS-3150-CP-30-RR-S4 | OPS-3150-ON-30-RR-S4 | OPS-3150-OP-30-RR-S4 | |
| number of wires | 3 | 3 | 3 | 3 | |
| output stage | NPN TRANSISTOR | PNP TRANSISTOR | NPN TRANSISTOR | PNP TRANSISTOR | |
| output function | NC | NC | NO | NO | |
| switching distance | 150 cm | 150 cm | 150 cm | 150 cm | |
| voltage range | 10-30VDC | 10-30VDC | 10-30VDC | 10-30VDC | |
| max output current | 250 mA | 250 mA | 250 mA | 250 mA | |
| temperature range | -20~+60 °C | -20~+60 °C | -20~+60 °C | -20~+60 °C | |
| max output frequency | 500 Hz | 500 Hz | 500 Hz | 500 Hz | |
| indicator led | yes | yes | yes | yes | |
| max drop voltage | 2 V | 2 V | 2 V | 2 V | |
| influence protection | IP66 | IP66 | IP66 | IP66 | |
| revers voltage protection | yes | yes | yes | yes | |
| short circuit protection | no | no | no | no | |
| output | 4Pin SOCKET | 4Pin SOCKET | 4Pin SOCKET | 4Pin SOCKET | |
| circuit |  |  |  |  | |

Central office : No 36 , karimkhan ave. , darvazeh tehran , tabriz , iran ; zip code : 5157913399 ; P.O. box : 51575-5140
 Email : info@tabrizpeguh.com ; Website : www.tabrizpeguh.com ; Tel : +984133330490 ; Fax : +984133318200