


pre cabled 2 wire magnetic sensors

housing					
	M12X1Ni PLATED Brass	M12X1Ni PLATED Brass	M18X1Ni PLATED Brass	M18X1Ni PLATED Brass	REC. 10X20X40 PA or PP
code	MPS-210-C-12	MPS-210-O-12	MPS-210-C-18	MPS-210-O-18	MPS-210-C-R10
number of wires	2	2	2	2	2
output stage	REED RELAY	REED RELAY	REED RELAY	REED RELAY	REED RELAY
output function	NC	NO	NC	NO	NC
switching distance	10 mm	10 mm	10 mm	10 mm	10 mm
voltage range	10-250VACDC	10-250VACDC	10-250VACDC	10-250VACDC	10-250VACDC
max output current	250 mA	250 mA	250 mA	250 mA	250 mA
temperature range	-20~+60 °C	-20~+60 °C	-20~+60 °C	-20~+60 °C	-20~+60 °C
max output ferequence	50 Hz	50 Hz	50 Hz	50 Hz	50 Hz
indicator led	yes	yes	yes	yes	yes
max drop voltage	no	no	no	no	no
max noload or leakage curtrent	no	no	no	no	no
influence protection	IP67	IP67	IP67	IP67	IP67
revers voltage protection	no	no	no	no	no
short circuit protection	no	no	no	no	no
output	CABLE2X0.25-1.5m	CABLE2X0.25-1.5m	CABLE2X0.35-1.5m	CABLE2X0.35-1.5m	CABLE2X0.25-1.5m
circuit					

pre cabled 2 wire magnetic sensors

housing					
	REC. 10X20X40 PA or PP				
code	MPS-210-0-R10				
number of wires	2				
output stage	REED RELAY				
output function	NO				
switching distance	10 mm				
voltage range	10-250VACDC				
max output current	250 mA				
temperature range	-20~+60 °C				
max output ferequence	50 Hz				
indicator led	yes				
max drop voltage	no				
max no-load or leakage current	no				
influence protection	IP67				
revers voltage protection	no				
short circuit protection	no				
output	CABLE2X0.25-1.5m				
circuit	