

4pin connector 2 wire magnetic sensors

housing					
	M12X1Ni PLATED Brass	M12X1Ni PLATED Brass	M18X1Ni PLATED Brass	M18X1Ni PLATED Brass	
code	MPS-210-C-12-S4	MPS-210-O-12-S4	MPS-210-C-18-S4	MPS-210-O-18-S4	
number of wires	2	2	2	2	
output stage	REED RELAY	REED RELAY	REED RELAY	REED RELAY	
output function	NC	NO	NC	NO	
switching distance	10 mm	10 mm	10 mm	10 mm	
voltage range	10-250VACDC	10-250VACDC	10-250VACDC	10-250VACDC	
max output current	250 mA	250 mA	250 mA	250 mA	
temperature range	-20~+60 °C	-20~+60 °C	-20~+60 °C	-20~+60 °C	
max output ferequence	50 Hz	50 Hz	50 Hz	50 Hz	
indicator led	yes	yes	yes	yes	
max drop voltage	no	no	no	no	
max noload or leakage curtrent	no	no	no	no	
influence protection	IP67	IP67	IP67	IP67	
revers voltage protection	no	no	no	no	
short circuit protection	no	no	no	no	
output	4Pin SOCKET	4Pin SOCKET	4Pin SOCKET	4Pin SOCKET	
circuit					