











pre cabled speed pickup sensor

housing					
	M12STAINLESS STEEL 304	M12STAINLESS STEEL 304	M12STAINLESS STEEL 304	M14STAINLESS STEEL 304	M14STAINLESS STEEL 304
code	IPS-201-S-12	IPS-301-SA-12-N	IPS-301-SA-12-P	IPS-201-S-14	IPS-301-SA-14-N
number of wires	2	3	3	2	3
output type	AC SIGNAL	SQUARE PULSE	SQUARE PULSE	AC SIGNAL	SQUARE PULSE
switching distance	1mm	1mm		1mm	1mm
temperature range	-20~+60 °C	-20~+60 °C	-20~+60 °C	-20~+60 °C	-20~+60 °C
influence protection	IP67	IP67	IP67	IP67	IP67
output	CABLE2X0.25-1.5m	CABLE3X0.25-1.5m	CABLE3X0.25-1.5m	CABLE2X0.25-1.5m	CABLE3X0.25-1.5m
output stage		NPN TRANSISTOR	PNP TRANSISTOR		NPN TRANSISTOR
output function		NC	NC		NC
voltage range		10-30VDC	10-30VDC		10-30VDC
max output current		50 mA	50 mA		50 mA
max output ferequence	20KHz	20KHz	20KHz	20KHz	20KHz
indicator led	no	yes	yes	no	yes
max noload or leakage curtrent		10 mA	10 mA		10 mA
circuit					

pre cabled speed pickup sensor

housing					
	M14STAINLESS STEEL 304	M18STAINLESS STEEL 304	M18STAINLESS STEEL 304	M18STAINLESS STEEL 304	
code	IPS-301-SA-14-P	IPS-201-S-18	IPS-301-SA-18-N	IPS-301-SA-18-P	
number of wires	3	2	3	3	
output type	SQUARE PULSE	AC SIGNAL	SQUARE PULSE	SQUARE PULSE	
switching distance	1mm	1mm	1mm	1mm	
temperature range	-20~+60 °C	-20~+60 °C	-20~+60 °C	-20~+60 °C	
influence protection	IP67	IP67	IP67	IP67	
output	CABLE3X0.25-1.5m	CABLE2X0.25-1.5m	CABLE3X0.25-1.5m	CABLE3X0.25-1.5m	
output stage	PNP TRANSISTOR		NPN TRANSISTOR	PNP TRANSISTOR	
output function	NC		NC	NC	
voltage range	10-30VDC		10-30VDC	10-30VDC	
max output current	50 mA		50 mA	50 mA	
max output ferequence	20KHz	20KHz	20KHz	20KHz	
indicator led	yes	no	yes	yes	
max noload or leakage curtrent	10 mA		10 mA	10 mA	
circuit					