
























4pin connector namur sensors

housing					
	M12X1Ni PLATED Brass	M12X1Ni PLATED Brass	M14X1Ni PLATED Brass	M14X1Ni PLATED Brass	M18X1Ni PLATED Brass
code	IPS-202-NM-12-S4	IPS-204-NM-12-S4	IPS-203-NM-14-S4	IPS-205-NM-14-S4	IPS-205-NM-18-S4
number of wires	2	2	2	2	2
switching distance	2 mm	4 mm	3 mm	5 mm	5 mm
temperature range	-20~+60 °C	-20~+60 °C	-20~+60 °C	-20~+60 °C	-20~+60 °C
influence protection	IP67	IP67	IP67	IP67	IP67
output	4Pin SOCKET	4Pin SOCKET	4Pin SOCKET	4Pin SOCKET	4Pin SOCKET
output function	NAMUR	NAMUR	NAMUR	NAMUR	NAMUR
voltage range	8.2VDC	8.2VDC	8.2VDC	8.2VDC	8.2VDC
max output ferequence	1500 Hz	1500 Hz	1500 Hz	1000 Hz	1000 Hz
indicator led	no	no	no	no	no
mounting	flush(shielded)	non flush (unshielded)	flush(shielded)	non flush (unshielded)	flush(shielded)
circuit					

4pin connector namur sensors

housing					
	M18X1.5Ni PLATED Brass	M22X1.5Ni PLATED Brass	M22X1.5Ni PLATED Brass	M30X1.5Ni PLATED Brass	M30X1.5Ni PLATED Brass
code	IPS-208-NM-18-S4	IPS-208-NM-22-S4	IPS-210-NM-22-S4	IPS-210-NM-30-S4	IPS-215-NM-30-S4
number of wires	2	2	2	2	2
switching distance	8 mm	8 mm	10 mm	10 mm	15 mm
temperature range	-20~+60 °C	-20~+60 °C	-20~+60 °C	-20~+60 °C	-20~+60 °C
influence protection	IP67	IP67	IP67	IP67	IP67
output	4Pin SOCKET	4Pin SOCKET	4Pin SOCKET	4Pin SOCKET	4Pin SOCKET
output function	NAMUR	NAMUR	NAMUR	NAMUR	NAMUR
voltage range	8.2VDC	8.2VDC	8.2VDC	8.2VDC	8.2VDC
max output ferequence	1000 Hz	1000 Hz	700 Hz	700 Hz	500 Hz
indicator led	no	no	no	no	no
mounting	non flush (unshielded)	flush(shielded)	non flush (unshielded)	flush(shielded)	non flush (unshielded)
circuit					

4pin connector namur sensors

housing					
	M34X1.5Ni PLATED Brass	M34X1.5Ni PLATED Brass	M40X1.5Ni PLATED Brass		
code	IPS-215-NM-34-S4	IPS-220-NM-34-S4	IPS-220-NM-40-S4		
number of wires	2	2	2		
switching distance	15 mm	20 mm	20 mm		
temperature range	-20~+60 °C	-20~+60 °C	-20~+60 °C		
influence protection	IP67	IP67	IP67		
output	4Pin SOCKET	4Pin SOCKET	4Pin SOCKET		
output function	NAMUR	NAMUR	NAMUR		
voltage range	8.2VDC	8.2VDC	8.2VDC		
max output ferequence	500 Hz	300 Hz	300 Hz		
indicator led	no	no	no		
mounting	flush(shielded)	non flush (unshielded)	flush(shielded)		
circuit	