











Visible Light Optoelectronic sensors



housing					
	M18X1 PBT	M18X1 PBT	M18X1 PBT	M18X1 PBT	M18X1 Ni PLATED Brass
code	OPS-320-OP-P18-DF-VR	OPS-320-CP-P18-DF-VR	OPS-320-CN-P18-DF-VR	OPS-320-ON-P18-DF-VR	OPS-320-OP-18-DF-VR
number of wires	3	3	3	3	3
output stage	PNP TRANSISTOR	PNP TRANSISTOR	NPN TRANSISTOR	NPN TRANSISTOR	PNP TRANSISTOR
output function	NO	NC	NC	NO	NO
switching distance	20 cm	20 cm	20 cm	20 cm	20 cm
voltage range	10-30VDC	10-30VDC	10-30VDC	10-30VDC	10-30VDC
max output current	250 mA	250 mA	250 mA	250 mA	250 mA
temperature range	-20~+60 °C	-20~+60 °C	-20~+60 °C	-20~+60 °C	-20~+60 °C
max output ferequence	100 Hz				
indicator led	yes	yes	yes	yes	yes
max drop voltage	2 V	2 V	2 V	2 V	2 V
max currtrent consumption	yes				
influence protection	IP66	IP66	IP66	IP66	IP66
output	CABLE3X0.25-1.5m	CABLE3X0.25-1.5m	CABLE3X0.25-1.5m	CABLE3X0.25-1.5m	CABLE3X0.25-1.5m
circuit					

Central office : No 36 , karimkhan ave. , darvazeh tehran , tabriz , iran ; zip code : 5157913399 ; P.O. box : 51575-5140
 Email : info@tabrizpeguh.com ; Website : www.tabrizpeguh.com ; Tel : +984133330490 ; Fax : +984133318200

Visible Light Optoelectronic sensors

housing					
	M18X1 Ni PLATED Brass	M18X1 Ni PLATED Brass	M18X1 Ni PLATED Brass	M18X1 Ni PLATED Brass	M18X1 Ni PLATED Brass
code	OPS-320-ON-18-DF-VR	OPS-320-CN-18-DF-VR	OPS-320-CP-18-DF-VR	OPS-420-P-18-DF-VR	OPS-420-N-18-DF-VR
number of wires	3	3	3	4	4
output stage	NPN TRANSISTOR	NPN TRANSISTOR	PNP TRANSISTOR	PNP TRANSISTOR	NPN TRANSISTOR
output function	NO	NC	NC	NO+NC	NO+NC
switching distance	20 cm	20 cm	20 cm	20 cm	20 cm
voltage range	10-30VDC	10-30VDC	10-30VDC	10-30VDC	10-30VDC
max output current	250 mA	250 mA	250 mA	250 mA	250 mA
temperature range	-20~+60 °C	-20~+60 °C	-20~+60 °C	-20~+60 °C	-20~+60 °C
indicator led	yes	yes	yes	yes	yes
max drop voltage	2 V	2 V	2 V	2 V	2 V
influence protection	IP66	IP66	IP66	IP66	IP66
output	CABLE3X0.25-1.5m	CABLE3X0.25-1.5m	CABLE3X0.25-1.5m	CABLE4X0.25-1.5m	CABLE4X0.25-1.5m
circuit					

Visible Light Optoelectronic sensors

housing					
	M18X1 PBT	M18X1 PBT			
code	OPS-420-N-P18-DF-VR	OPS-420-P-P18-DF-VR			
number of wires	4	4			
output stage	NPN TRANSISTOR	PNP TRANSISTOR			
output function	NO+NC	NO+NC			
switching distance	20 cm	20 cm			
voltage range	10-30VDC	10-30VDC			
max output current	250 mA	250 mA			
temperature range	-20~+60 °C	-20~+60 °C			
indicator led	yes	yes			
max drop voltage	2 V	2 V			
influence protection	IP66	IP66			
output	CABLE4X0.25-1.5m	CABLE4X0.25-1.5m			
circuit	