




# IPS-210-CD-22-VI-S4

Category: 2wire DC 4pin connector inductive sensor



|                        |                               |
|------------------------|-------------------------------|
| IPS-210-CD-22-VI-S4    | Product Code                  |
| M22X1.5Ni PLATED Brass | housing                       |
| 2                      | number of wires               |
| 10 mm                  | switching distance            |
| -20~+60 °C             | temperature range             |
| IP66                   | influence protection          |
| 4Pin SOCKET            | output                        |
| TRANSISTOR             | output stage                  |
| NC                     | output function               |
| 10-60VDC               | voltage range                 |
| 250 mA                 | max output current            |
| 500 Hz                 | max output frequency          |
| ✓                      | indicator led                 |
| 5 V                    | max drop voltage              |
| 2 mA                   | max noload or leakage current |
| 3 bar                  | pressure rate                 |
| non flush (unshielded) | mounting                      |
| yes                    | revers voltage protection     |
| 0                      | short circuit protection      |
| yes                    | pick voltage protection       |

Address: No.36 , Karimkhan Ave , Darvazeh Tehran ,Tabriz-Iran

Postal Code : 5157913399 | Post Inbox : 5341-51575 | Phone : 33330490-041 | Fax : 33318200-041

Website : [www.tabrizpeguh.com](http://www.tabrizpeguh.com) | Email : [info@tabrizpeguh.com](mailto:info@tabrizpeguh.com)